



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number:

0 294 093 B1

12

EUROPEAN PATENT SPECIFICATION

49 Date of publication of patent specification: 01.09.93 51 Int. Cl.⁵: C13K 7/00

21 Application number: 88304743.3

22 Date of filing: 25.05.88

54 Process for preparing maltose powder.

30 Priority: 29.05.87 JP 135697/87

43 Date of publication of application:
07.12.88 Bulletin 88/49

45 Publication of the grant of the patent:
01.09.93 Bulletin 93/35

84 Designated Contracting States:
DE FR GB

56 References cited:
FR-A- 2 566 409
GB-A- 2 148 297

CHEMICAL ABSTRACTS, vol. 92, no. 6, February 1980, page 87, abstract no. 43564d, Columbus, Ohio, US

73 Proprietor: KABUSHIKI KAISHA
HAYASHIBARA SEIBUTSU KAGAKU KEN-
KYUJO
2-3, 1-chome, Shimoi-shi
Okayama-shi Okayama(JP)

72 Inventor: Sakai, Shuzo
3-41, 1-chome Ejiri-asahigaoka Seto-cho
Akaiwa-gun Okayama(JP)
Inventor: Akai, Hiroshi
101 Hanajiri
Okayama-shi Okayama(JP)
Inventor: Miyake, Toshio
7-10-403, 1-chome Okuda
Okayama-shi Okayama(JP)

74 Representative: Pendlebury, Anthony et al
PAGE, WHITE & FARRER 54 Doughty Street
London WC1N 2LS (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

The present invention relates to a process for preparing maltose powder, specifically, to a process for preparing a stable maltose powder containing crystalline beta-maltose hydrate.

As disclosed, for example, in Japanese Patent Publication No. 3,937/79 and Japanese Patent Laid-Open No. 92,299/85, maltose powders containing crystalline beta-maltose hydrate have been manufactured by concentrating a high-purity maltose liquid to about 70-80 w/w % (moisture content of 20-30 w/w %), adding a seed crystal to the syrup, spray-drying a massecuite wherein crystallization of beta-maltose hydrate has proceeded to 30-50%, and ageing the resultant powder to a moisture content of 6 w/w %.

Conventional processes, however, have the drawback that they consume a relatively large amount of energy for drying at ambient temperature a maltose syrup having a relatively high moisture content (i.e. 20-30 w/w %) wherein crystallization of beta-maltose hydrate has been initiated by the addition of a seed crystal and this increases the manufacturing cost of maltose powder, and in addition to the disadvantage that a vigorous heating during the drying undesirably melts the resultant crystalline beta-maltose hydrate to hinder the attainment of a consistently high-quality maltose powder.

In order to overcome these drawbacks of the conventional processes, the present inventors studied various conditions for crystallizing beta-maltose hydrate in a syrup having the highest possible concentration. As a result, the present inventors found that the crystallization rate at ambient temperature is not necessarily increased as the saturation degree in the syrup is elevated; as well as that the crystallization rate is maximized when the moisture content of the syrup is in the range of 20-30 w/w % and a moisture content out of this range retards the crystallization rate.

Also was found that crystallization of beta-maltose hydrate in a high-concentration syrup having a moisture content below 10 w/w %, specifically, about 5-8 w/w %, which is comparable to that of commercial maltose powder is not recommendable in industrial-scale preparation of maltose powder.

While, as disclosed in Japanese Patent Laid-Open No.35,800/86, it has been known that a syrup having a moisture content below 10 w/w % tends to yield crystalline alpha-maltose.

By utilizing this, the present inventors discovered that the crystallization of beta-maltose hydrate can be accelerated by partially crystallizing anhydrous alpha-maltose in a high-concentration syrup having a moisture content below 10 w/w %, preferably, about 5-8 w/w %, to increase the moisture

content in its remaining amorphous part. Based on an additional finding that ageing of a crystalline alpha-maltose containing massecuite accelerates and facilitates both crystallization of beta-maltose hydrate and conversion of the crystalline alpha-maltose into crystalline beta-maltose hydrate, the present inventors established a novel process that enables industrial-scale preparation of a stable powder containing crystalline beta-maltose hydrate from a high-concentration syrup having a moisture content below 10 w/w %.

Accordingly the present invention provides a process for preparing maltose powder, comprising concentrating an aqueous solution of a high-purity maltose having a maltose content of at least 85 w/w %, on a dry substance basis, into a high concentration syrup having a moisture content below 10 w/w %;

allowing the resultant high-concentration syrup first to crystallize alpha-maltose in the presence of a seed crystal; and

allowing the resultant mixture to crystallize beta-maltose hydrate while converting the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate.

The wording "high-purity maltose" used in this specification means maltose having a maltose content of at least 80% DS (dry substance), preferably, 85% DS in order to obtain a satisfactorily stable maltose powder. To prepare such high-purity maltose from starch, a method as disclosed, for example, in Japanese Patent Publications Nos. 11,437/81 and 17,078/81, wherein gelatinized-or liquefied-starch is subjected to the action of beta-amylase and the released maltose is separated from polymer dextrans; and a method as disclosed, for example, in Japanese patent Publications Nos. 13,089/72 and 3,938/79, wherein gelatinized-or liquefied-starch is subjected to beta-amylase and a starch debranching enzyme such as isoamylase and beta-amylase are employable.

The maltose content of the obtained high-purity maltose is augmentable by subjecting the contaminant saccharides, such as maltotriose, to an enzyme as disclosed, for example, in Japanese Patent Publications Nos.28,153/81, 3,356/82 and 28,154/81, or by removing the contaminant saccharides with a fractionation as disclosed, for example, in Japanese Patent Laid-Open No.23,799/83 using a column of strongly-acidic cation exchange resin. Such fractionation can be effected by the fixed bed-, moving bed- or simulated moving bed-method.

To concentrate an aqueous solution of the obtained high-purity maltose having a maltose content of at least 80% DS, preferably, 85% DS or higher, to a high-concentration syrup, desirably, the lowest possible cost procedure, for example, concentra-

tion in vacuo, is employed.

Such aqueous solution is prepared into a high-concentration syrup having a moisture content below 10 w/w %, preferably, about 5-8 w/w %, which is first kept at a temperature in the range of 50-130 °C in the presence of a seed crystal to partially crystallize alpha-maltose, then aged at a temperature in the range of 10-70 °C to crystallize beta-maltose hydrate while converting the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate. The present inventors found that, when added to a syrup having a moisture content of 10 w/w % or higher, specifically, 12 w/w % or higher but lower than 25 w/w %, crystalline alpha-maltose dissolves in the syrup and substantially does not crystallize it, as well as that beta-maltose hydrate is much more crystallizable in such syrup.

Also was found that the presence of crystalline alpha-maltose in a high-concentration syrup having a moisture content below 5 w/w % is unfavorable because it requires addition of water to convert the crystalline alpha-maltose into crystalline beta-maltose hydrate.

An appropriate temperature for crystallizing alpha-maltose is 50-130 °C, preferably, 60-120 °C. An appropriate temperature for crystallizing beta-maltose hydrate and for converting crystalline alpha-maltose into crystalline beta-maltose hydrate is 10-80 °C, preferably, 20-70 °C.

Seed crystals may be added to accelerate the crystallization of maltose: Crystalline alpha-maltose, preferably, a mixture of crystalline alpha-maltose and crystalline beta-maltose hydrate is added as the seed crystal to a high-concentration syrup of a high-purity maltose in an amount of 0.001-20% DS, preferably, 0.1-5% DS, for example, by contacting, mixing and kneading.

To prepare the resultant syrup into a powder containing crystalline beta-maltose hydrate, for example, extrusion granulation and block pulverization are employable. In the case of the extrusion granulation, for example, while keeping at a temperature in the range of 60-120 °C, a high-concentration syrup of a high-purity maltose having a moisture content below 10 w/w % is kneaded together with a mixture of crystalline alpha-maltose and crystalline beta-maltose hydrate to effect a partial crystallization of alpha-maltose, and the resultant is fed to an extrusion granulator to obtain a granular masseccuite or a granular powder which is then aged at a temperature in the range of 20-70 °C to crystallize beta-maltose hydrate and also to convert the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate.

Alternatively, such a high-concentration syrup is kneaded together with a crystalline alpha-maltose seed while keeping at a temperature in the range of 60-120 °C, and the resultant mixture is

passed through an extrusion granulator while accelerating crystallization of alpha-maltose. The obtained granular masseccuite is allowed to contact with a crystalline beta-maltose hydrate seed, and then aged at a temperature in the range of 20-70 °C to accelerate both crystallization of beta-maltose hydrate and conversion of the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate. Thus, a maltose powder containing crystalline beta-maltose hydrate is obtainable.

In the block pulverization, for example, a high-concentration syrup of a high-purity maltose having a moisture content below 10 w/w % is placed in a crystallizer, and mixed with a blend of crystalline alpha-maltose and crystalline beta-maltose hydrate while accelerating crystallization of alpha-maltose by keeping at a temperature in the range of 60-120 °C. The resultant masseccuite is then transferred in a plastic tray, aged and solidified at a temperature in the range of 20-70 °C. The resultant block is cut and scraped with a cutting machine and/or a hammer mill to obtain a maltose powder containing crystalline beta-maltose hydrate. If necessary, moisture controlling, dehydrating and/or screening steps can be provided before or after the pulverizing step.

Since the obtained maltose powder having a moisture content approximately equal to that of the starting high-concentration syrup requires no or much less energy for postcrystallization drying, a consistently high-quality maltose powder can be manufactured at a reduced drying cost.

The mildly sweet white powder thus obtained is advantageously usable as a sweetener in various foods and beverages, as well as a humectant, vehicle or stabilizer in cosmetics, toiletries, pharmaceuticals and chemicals.

Several embodiments of the present invention will hereinafter be explained.

Example 1

A liquefied starch solution having a DE (Dextrose Equivalent) of about 0.5 was prepared by adding to a suspension of 1 part by weight of potato starch in 10 parts by weight of water a commercial bacterial liquefying alpha-amylase (EC 3.2.1.1), heating the mixture to 90 °C to effect gelatinization, and further heating it quickly to 130 °C to suspend enzymatic reaction. To the solution was added 100 units/g starch of isoamylase (EC 3.2.1.68) prepared from a culture of *Pseudomonas amyloclavata* ATCC 21262, and 50 units/g starch of "#1500", a beta-amylase (EC 3.2.1.2) derived from soybean, commercialized by Nagase & Company, Ltd., Osaka, Japan, and the resultant mixture was saccharified at pH 5.0 for 40 hours to obtain a high-purity maltose having a

maltose content of 92.5% DS. The high-purity maltose was then purified by carbon decolorization and resin refining, and concentrated in vacuo to obtain a high-concentration syrup having a moisture content of 6.5 w/w %. The syrup was then placed in a kneader, and added with 1% DS crystalline alpha-maltose and 1% DS crystalline beta-maltose hydrate while keeping at 95 °C. The resultant mixture was then kneaded for 3 minutes at this temperature, extruded in sheet shape, aged at 80 °C for 3 hours, further aged at 40 °C for 48 hours, and pulverized to obtain a maltose powder containing crystalline beta-maltose hydrate, moisture content of about 6.0 w/w %, in a yield of about 94% DS against the starting starch.

The product in the form of a non-hygroscopic stable powder is advantageously usable as a sweetener having a perceived sweetness value of about 1/3 compared to sucrose in a variety of foods and beverages.

Furthermore, the product is advantageously usable as a humectant, vehicle or stabilizer in cosmetics, toiletries, pharmaceuticals and chemicals.

Example 2

An aqueous solution of a high-purity maltose having a maltose content of 92.5% DS, obtained by the method in Example 1, was prepared into a high-concentration syrup having a moisture content of 5.8 w/w %. The syrup was then mixed with 2% DS crystalline alpha-maltose, and the mixture was granulated with an extrusion granulator. After ageing at 70 °C for 5 hours, the resultant granules were added with 2% DS crystalline beta-maltose, and the mixture was aged at 40 °C for 30 hours to obtain a maltose powder containing crystalline beta-maltose hydrate, moisture content of 5.3 w/w %, in a yield of about 95% DS against the starting starch.

Similarly as the product in Example 1, the product in the form of a stable powder free of moisture uptake is advantageously usable in foods, beverages, cosmetics, toiletries and pharmaceuticals.

Example 3

A suspension of 2 parts by weight of corn starch in 10 parts by weight of water was added with a commercial bacterial alpha-amylase, and the mixture was heated to 93 °C to effect liquefaction, followed by heating to 130 °C to suspend enzymatic reaction. The resultant liquefied starch solution having a DE of about 2 was quickly cooled to 55 °C, and then added with isoamylase (EC 3.2.1.68) and a soybean beta-amylase in respective amount of 120 units/g starch and 100 units/g

starch. The mixture was kept at pH 5.0 for 36 hours to effect saccharification, purified and concentrated similarly as in Example 1 to obtain a high-concentration syrup having a maltose content of about 88.2% DS and a moisture content of 6 w/w %. The syrup was then placed in a crystallizer, and added with 1% DS crystalline alpha-maltose seed and 1% DS crystalline beta-maltose hydrate seed at 90 °C. After mixing for 5 minutes while keeping at this temperature, the resultant was transferred to plastic trays, and aged first at 70 °C for 10 hours then at 40 °C for 48 hours to obtain a masseccuite solid in block shape. The masseccuite solid was then cut and scraped with a pulverizer, and screened to obtain a maltose powder containing crystalline beta-maltose hydrate, moisture content of about 5.5 w/w %, in a yield of about 92% DS against the starting corn starch.

The masseccuite solid was free of deformation and cracking, and exerted a satisfactory pulverizability.

Similarly as the product in Example 1, the product in the form of a stable powder free of moisture uptake is advantageously usable in foods, beverages, cosmetics, toiletries and pharmaceuticals.

As described above, the present invention relates to a process for preparing a maltose powder containing crystalline beta-maltose hydrate from a high-concentration syrup having a moisture content below 10 w/w % which has been deemed hardly crystallizable. More particularly, the preparation of such maltose powder is facilitated by concentrating an aqueous solution of a high-purity maltose having a maltose content above 85 w/w % into a high-concentration syrup having a moisture content below 10 w/w %, crystallizing alpha-maltose in the presence of a crystalline alpha-maltose seed, and crystallizing beta-maltose hydrate while converting the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate.

Since in the invention the postcrystallization drying can be carried out with no or much less amount of energy by concentrating in vacuo a high-concentration syrup to a moisture content approximately equal to a desired end product and this cuts a large amount energy for drying, consistently high-quality maltose powders are obtainable at a reduced drying cost. Thus, the present invention is very significant in the art.

The maltose powder obtained in this way is advantageously and extensively usable as a sweetener, humectant, vehicle or stabilizer in foods, beverages, cosmetics, toiletries, pharmaceuticals and chemicals.

Claims

1. A process for preparing maltose powder, comprising concentrating an aqueous solution of a high-purity maltose having a maltose content of at least 85 w/w %, on a dry substance basis, into a high-concentration syrup having a moisture content below 10 w/w %;
allowing the resultant high-concentration syrup first to crystallize alpha-maltose in the presence of a seed crystal; and
allowing the resultant mixture to crystallize beta-maltose hydrate while converting the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate.
2. A process according to claim 1, wherein said high-concentration syrup has a moisture content in the range of 5.0-8.0 w/w %.
3. A process according to claim 1 or 2, wherein crystalline alpha-maltose is used alone or in combination with crystalline beta-maltose hydrate as the seed crystal.
4. A process according to claim 1, 2 or 3, wherein crystallization of alpha-maltose is effected at a temperature in the range of 60-120 °C, while crystallization of beta-maltose hydrate and conversion of the resultant crystalline alpha-maltose into crystalline beta-maltose hydrate are effected at a temperature in the range of 20-70 °C.

Patentansprüche

1. Verfahren zur Herstellung von Maltosepulver, bei dem eine wäßrige Lösung einer hochreinen Maltose mit einem Maltosegehalt von mindestens 85 Gew.-% auf einer Trockensubstanzbasis in einen hochkonzentrierten Sirup mit einem Feuchtigkeitsgehalt unterhalb 10 Gew.-% konzentriert wird;
man zuerst ein Kristallisieren des erhaltenen hochkonzentrierten Sirups zu Alpha-Maltose in Anwesenheit eines Impfkristalls ermöglicht; und
man ein Kristallisieren der erhaltenen Mischung zu Beta-Maltosehydrat ermöglicht, während die erhaltene kristalline Alpha-Maltose in kristallines Beta-Maltosehydrat umgesetzt wird.
2. Verfahren nach Anspruch 1, bei dem der hochkonzentrierte Sirup einen Feuchtigkeitsgehalt im Bereich von 5,0 bis 8,0 Gew.-% aufweist.

3. Verfahren nach Anspruch 1 oder 2, bei dem kristalline Alpha-Maltose allein oder in Kombination mit kristallinem Beta-Maltosehydrat als Impfkristall verwendet wird.

4. Verfahren nach Anspruch 1, 2 oder 3, bei dem die Kristallisierung der Alpha-Maltose bei einer Temperatur im Bereich von 60 - 120 °C bewirkt wird, während die Kristallisierung des Beta-Maltosehydrats und die Umsetzung der erhaltenen kristallinen Alpha-Maltose in kristallines Beta-Maltosehydrat bei einer Temperatur im Bereich von 20 - 70 °C bewirkt wird.

Revendications

1. Procédé de préparation de poudre de maltose, comprenant les étapes consistant à concentrer une solution aqueuse de maltose très pur, ayant une teneur en maltose d'au moins 85 % en poids, sur la base de la substance sèche, en un sirop de concentration élevée, ayant une teneur en humidité de moins de 10 % en poids ;
d'abord laisser cristalliser le sirop résultant, de concentration élevée, en alpha-maltose, en présence d'un germe cristallin ; et
laisser cristalliser le mélange résultant en hydrate de bêta-maltose, tout en transformant l'alpha-maltose cristallin résultant en hydrate de bêta-maltose cristallin.
2. Procédé selon la revendication 1, dans lequel ledit sirop de concentration élevée a une teneur en humidité comprise entre 5,0 et 8,0 % en poids.
3. Procédé selon la revendication 1 ou 2, dans lequel l'alpha-maltose cristallin est utilisé seul ou combiné avec de l'hydrate de bêta-maltose cristallin en tant que germe cristallin.
4. Procédé selon la revendication 1, 2 ou 3, dans lequel on effectue la cristallisation de l'alpha-maltose à une température comprise entre 60 et 120 °C, alors qu'on effectue la cristallisation de l'hydrate de bêta-maltose et la transformation de l'alpha-maltose cristallin résultant en hydrate de bêta-maltose cristallin à une température comprise entre 20 et 70 °C.